

ARMORGUARD CLEANER
DIRECTIONS FOR USE

This is a combination cleaner and surface preparation for concrete that is going to be coated.

NOTE: This can irritate eyes and skin, flush immediately with warm water if contact is made. This product will etch aluminum and glass. Do not empty into storm drains, rivers or streams. **Do not ingest.**

DIRECTIONS FOR USE

Mix one cup of powder to 1 gallon of water (warm water dissolves quickly) each gallon treats 300-350 square feet.

Apply on approximately ten square feet at a time. Do not allow product to dry, must remain wet for 10 minutes Minimum to 30 minutes Maximum. Do not allow to puddle.

Scrub with a stiff bristle brush (preferably a powdered Nylon brush 80 grit) in all directions.

After 10 minutes Minimum, powerwash or hose with lots of clean water. Vacuuming the surface will remove particles other wise left behind.

NOTE: If areas appear unclean, oily or contaminated, repeat. Dry powder can be applied directly to the area.

The Component in the is chemical that converts calcium hydroxide to a calcium silicate does so in the presence of water, do not allow it to dry out for a minimum of 10 minutes.

Done properly, this process will increase the adhesion of coatings to concrete, by converting the powdery calcium hydroxide in the concrete to calcium silicate with the pores.

There is NO warranty, expressed or implied, end user is responsible for its proper usage, and manufacturer/distributor is not responsible for consequential or non-consequential damages.

If you have any questions or concerns, please contact us at 1-888-ECO-EPOXY, or visit us on the web at www.ecosmartepoxysystems.com.